

TSS130E is designed for the processing of insulated and uninsulated single core, multicore and flat cables. The machine counts the batch, measures the cutting length, strips and unjackets with special blades into a long comb. Through an easy-to-use control panel with a 10-inch color touchscreen display, the operator can constantly overview the work in progress, set and correct batch parameters, and receive batch information.

TSS130E is equipped for inline processing with other Samec machines, including motorized cable dereelers, pre-feeders, wire markers and stackers – the machines are connected through a cable to the various interfaces, allowing signal exchange between machines and the management of a single production line.

Manufactured using high quality methods and materials, the machine guarantees long term durability. The case is constructed in welded metal and all mechanical details are treated to prevent environmental oxidation. Electronic parts are produced with reliability and functionality in mind, using high integration components, while the top quality pneumatic parts can be easily found in Europe and abroad. The electrical system conforms to EN60204-1 industry regulations.



SAMEC MACCHINE reserves the right to modify its product contents and technical data without prior notice. This document is property of SAMEC MACCHINE in Vicenza, Italy.

Italian Technology Quality



Samec Macchine s.r.l. Via delle Prese, 45 36014 Santorso (VI) - Italy T 0445.576149 F 0445.501255 service@samecmacchine.it www.samecmacchine.it A Company of





Some details

TECHNICAL SPECIFICATIONS

Data setup		by touch display
Programmable quantity of pieces		Max 9999 pezzi
Lots		Max 9999
Max number of cables that can be store		1000 Cables (50 Clients - 20 cables per client)
Workable length		Min. 70mm – max. 500m
machine pass		15x15mm
Workable dia.		Min. 1mm – max 16mm
Workable strap width		Max 14mm
Maximum cutting section of the flexible multipolar conductor		50mm ²
Max displacement of the insulation		40mm
Stripping length on single core cables		Min 3mm
Stripping length	Tot	Max 280mm
	On one side	Max 160mm
	other side	Max 120mm
Programmable stripping length		Max 9999mm
Programmable length of the stripping sections		Max 9999mm
Feed speed		Variable 2.3m/s
Power		220/230v - 50/60hz
Air supply		6-8 Bar continuos
Power supply-absorption		1kw



Inline assembly example: 1 Motorized dereelers

- 2 Cut, strip & unjacket machine
- 3 Stacker

SAMEC MACCHINE reserves the right to modify its product contents and technical data without prior notice. This document is property of SAMEC MACCHINE in Vicenza, Italy.



Samec Macchine s.r.l. Via delle Prese, 45 36014 Santorso (VI) - Italy **T** 0445.576149 **F** 0445.501255 service@samecmacchine.it www.samecmacchine.it



